

TNMG-R/L

Product Images



R/L

—— Chip-breaker ——

Summary

ZANHO TNMG1604-S is a professional **triangular negative turning insert** specifically engineered for **Medium Machining**. Featuring the specialized **S chipbreaker** (modified from FS), it delivers

excellent chip control and edge stability. Available in both **Right-hand (R)** and **Left-hand (L)** orientations to meet diverse CNC profiling requirements.

Content

Key Performance & Features

- **S Chipbreaker (Medium Machining):** Optimized for stable chip evacuation at medium feed rates, preventing surface damage and ensuring process reliability.
- **R/L Orientation:** Specifically designed for profiling operations with dedicated Right-hand and Left-hand geometries for precise cutting paths.
- **Negative Triangular Geometry:** Provides high edge strength and multiple cutting edges, offering exceptional cost-efficiency in high-production turning.
- **Balanced Cutting Force:** The S profile ensures smooth cutting action even in materials prone to work hardening like stainless steel.

Technical Specifications

Model	Hand	Feed (fn)	Cut Depth (ap)
TNMG160404L-S	Left (L)	0.15 - 0.30	0.8 - 3.0 mm
TNMG160404R-S	Right (R)	0.15 - 0.30	0.8 - 3.0 mm
TNMG160408L-S	Left (L)	0.20 - 0.40	1.0 - 3.5 mm
TNMG160408R-S	Right (R)	0.20 - 0.40	1.0 - 3.5 mm

Need Help Selecting the Right Grade?

Our sales team can recommend the optimal grade based on your workpiece material and machining conditions.

Need Help Selecting the Right Grade?

Our sales team can recommend the optimal grade based on your workpiece material and machining conditions.

[? Back](#)

Thank you for your response. ?

.

Company Name(required)

Email(required)

website

Email

•

Submit