

VNMG-TF1

Product Images



TF1

—— Chip-breaker ——

Summary

ZANHO VNMG1604-TF1series is a professional **35° rhombic negative turning insert** specifically designed for **Medium Machining**. Featuring the specialized **TF1 chipbreaker**, it delivers stable

cutting performance and consistent chip evacuation at medium feed rates, making it ideal for the versatile turning of steel and alloy components with superior stability.

Content

Key Performance & Features

- **Medium Machining Excellence:** Optimized for semi-roughing to medium finishing applications, ensuring continuous productivity in general CNC turning.
- **TF1 Chipbreaker Geometry:** Specifically engineered for stable chip breaking at medium feed rates, effectively preventing chip nesting and surface damage.
- **Rhombic Stability:** The VNMG 35-degree rhombic design provides excellent clearance for complex profiling, multi-directional turning, and reaching narrow workpiece sections.
- **Strong Cutting Edge:** Enhanced edge toughness allows for stable machining even in slightly interrupted cuts or with varying depths of cut.

Technical Specifications

Model	Radius (re)	Feed (f)	Cut Depth (ap)
VNMG160404-TF1	0.4 mm	0.15 - 0.3 mm/r	1.0 - 4.0 mm
VNMG160408-TF1	0.8 mm	0.15 - 0.3 mm/r	1.0 - 4.0 mm

Need Help Selecting the Right Grade?

Our sales team can recommend the optimal grade and coating based on your specific material hardness and workpiece complexity.

[? Back](#)

Thank you for your response. ?

????(required)

??(required)

??

??

•

Submit